

Fire hydrant series

消防栓系列



Above ground fire hydrant

地上式消防栓

Pressure Rating 壓力等級	Norminal 標稱口徑	Shell Material 閥體材質	Outlet Size 出水口接頭尺寸
7.5K/10K/16K 125LB/150LB/250LB/300LB PN10/PN16/PN25	100mm(4")	Ductile Cast Iron 球墨鑄鐵	2 1/2" X1 2 1/2" X2
	150mm(6")		2 1/2" X1 4" X1



Above ground fire hydrant anti-collision type (Additional exhaust valve is possible)

地上式消防栓防撞型(可附加排氣閥)

Pressure Rating 壓力等級	Norminal 標稱口徑	Shell Material 閥體材質	Outlet Size 出水口接頭尺寸
7.5K/10K/16K 125LB/150LB/250LB/300LB PN10/PN16/PN25	100mm(4")	Ductile Cast Iron 球墨鑄鐵	2 1/2" X1 2 1/2" X2
	150mm(6")		2 1/2" X1 4" X1



Underground fire hydrant

地下式消防栓

Pressure Rating 壓力等級	Norminal 標稱口徑	Shell Material 閥體材質	Outlet Size 出水口接頭尺寸
7.5K/10K/16K 125LB/150LB/250LB/300LB PN10/PN16/PN25	75mm~100mm 3"~4"	Ductile Cast Iron 球墨鑄鐵	2 1/2" X1 2 1/2" X2
	150mm(6")		2 1/2" X1 4" X1

